bale



double disc distributors, with gap sowing system



STANDARD EQUIPMENT

- » working width 10÷24 m (MS, MX 850-1600)
- » working width 10÷36 m (MX 3000)
- » sieves in the hopper
- » indicator of angle of inclination of the spreader
- » spreading and setting tables
- » shield for border spreading

PRICE

MX 850 MX 1200 **MX** 1600

MX 3000

ACCESSORIES AT EXTRA CHARGE

spreader hopper made of stainless steel, 850 MX

spreader hopper made of stainless steel, 1200 MX

spreader hopper made of stainless steel, 1600 MX

two-line hydraulic control of the LH or RH side of spreading

rack tilt, MX

plate for limit spreading

removable transport wheels

lighting installation

PTO shaft for MS, MX 850, MX 1200 & MX 1600

PTO shaft for MX 3000

limiter for border spreading of granular fertilizers – mechanically folded



Limiter for MX

Limiter for border spreading allows obtaining the best precision of spreading at the border of fields in a simple manner.



Simple adjustment of the spreader

In our spreaders, adjustment of the working width and rate can be performed without the use of any tools. By the use of screws with convenient handles, adjustment of working width is not a problem.



LM spinner discs

Spinner discs are an important component of spreaders. Our fertilizer and lime spreaders have the spinner discs made of the best stainless steel grade. The LM fertilizer spinner discs ensure precise distribution of fertilizer in any conditions. Simple change of working width due to practical holes reduces the time for preparation the machine to work to minimum.

Туре	MX 850h	MX 1200h	MX 1600h	MX 3000h
Hopper capacity [dm³]	850	1 200	1 600	3 000
Operating width [m]	10 ÷ 24			10 ÷ 36
Length [m]	1,1		1,54	1,67
Width [m]	2		2,2	2,67
Loading height [m]	1,06	1,19	1,36	1,78
Weight [kg]	273	305	380	595
Power demand [HP]	60 ÷ 70	80 ÷ 90	100 ÷ 120	180